

ELECTROMECHANICAL METAL SHEET GRAB

TECHNICAL CHARACTERISTICS:

- Motor-Reducer with integrated torque limiter
- For all types of packet dimensions, weight and goods.
- Minimum loss of height
- Power supply 380 V 50 Hz.
- Safety sensors for avoiding opening of legs while transporting a load
- Robust steel structure with high elastic limit
- Several optionals



OPTIONALS:

- Implementation of weighing system with accuracy $\pm 0,1\%$
- Implementation of motorized rotation (355°) for a smooth positioning of load
- Telescopic extendable arms for handling of different packet lengths
- Radio remote control for tong or tong and crane
- Storage chair for tong
- Cable reel for power supply 380 V 50 Hz.

DATA TO ASK FOR OFFER:

- Max weight of packets
- Dimensions of packets
 - Length Máx. [$L_{\text{Máx.}}$: _____]
 - Length mín. [$L_{\text{mín.}}$: _____]
 - Width Máx. [$W_{\text{Máx.}}$: _____]
 - Width mín. [$W_{\text{mín.}}$: _____]
 - Height Máx. [$H_{\text{Máx.}}$: _____]
 - Height mín. [$H_{\text{mín.}}$: _____]
- Hook number in crane
- Working conditions (indoor – outdoor)